

MARITRANS®RELEASE AGENT

TECHNICAL DATA SHEET Date: 01.06.2017 - Version 17

Release agent for sandcarpet coatings

Product description

MARITRANS® RELEASE AGENT is a transparent, low odor, release agent that allows easy application of sandcarpet finishes, without having the sandcarpet mix stick on the trowel.

By this way a quick, smooth and effective application

MARITRANS® RELEASE AGENT is an integral part of MARITRANS® sandcarpet system.

The MARITRANS® RELEASE AGENT is used as a release agent for MARITRANS® sandcarpet coating application.

The MARITRANS® RELEASE AGENT is specially designed for MARITRANS[®] sandcarpet applications and is not suitable for any other use.

Advantages

- Simple application.
- Enables sandcarpet coating application.
- Low odor
- Highly effective

Consumption

10% by weight calculated on the MARITRANS® quantity used as binder in the sandcarpet coating mix.

This coverage is based on application in optimum conditions. Factors like temperature and moisture can alter consumption.

Application

Mix the MARITRANS® RELEASE AGENT with MARITRANS® and colored silica sand at indicated quantities for sandcarpet coating applications.

Packaging

MARITRANS® RELEASE AGENT is supplied in 1kg pails. Pails should be stored in dry and cool rooms for up to 9 months. Protect the material against moisture, frost and direct sunlight. Storage temperature: 5º-30ºC. Products should remain in their original, unopened containers, bearing the manufacturers name, product designation, batch number and application precaution labels.

Safety measures

See information supplied by the manufacturer. Please study the Safety Data sheet. PROFESSIONAL USE ONLY.





Our technical advice for use, whether verbal, written or in tests, is given in good faith and reflect the current level of knowledge and experience with our products. When using our products, a detailed object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults; correct application of our products herefore falls entirely within your scope of liability and responsibility. We will, of course, provide products of consistent quality within the scope of our General Conditions of lead and Delivery. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. Values in this technical data sheet are given as examples and may not be regarded as specifications. For product specifications contact our R+D department. The new edition of the technical data sheet supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practice.























